CTOLIGHTING

GAIA WALL TALL - WALL PLATE

FINISH

bronze with matt opal glass bronze with shiny opal glass bronze with smoked glass bronze with smoked hand formed glass satin brass with matt opal glass satin brass with shiny opal glass satin brass with smoked glass shade satin brass with smoked hand formed glass

DIMENSIONS (body of fixture)

 $150 \times 183 \times 350 \text{ mm} (w \times d \times h)$

WEIGHT

1.5kg (3.3lbs)

ILLUMINATION

220-240v - 1 x E14 - 25w max (or 4.5w 2700k LED) 110-130v - 1 x E12 - 25w max (or 4.5w 2700k LED)

DIMMING

dimmable bulb required trailing edge dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only)

WALL ROSE / PLATE

round wall plate - ø 114 x 5 mm (dia x d)

CERTIFICATION





*Diagrams are not to scale.





183mm (7.2)





150mm (5.9)





	-	
0	² □	:

SKU NUMBER	FINISH DESCRIPTION	VOLTAGE
GAIWATBZMO-PL-240	bronze with matt opal	220 - 240V
GAIWATBZOG-PL-240	bronze with shiny opal	220 - 240V
GAIWATBZSG-PL-240	bronze with smoked	220 - 240V
GAIWATBZHF-PL-240	bronze with smoked hand formed glass	220 - 240V
GAIWATSBMO-PL-240	satin brass with matt opal	220 - 240V
GAIWATSBOG-PL-240	satin brass with shiny opal	220 - 240V
GAIWATSBSG-PL-240	satin brass with smoked	220 - 240V
GAIWATSBHF-PL-240	satin brass with smoked hand formed glass	220 - 240V
GAIWATBZMO-PL-110	bronze with matt opal	110 - 130V
GAIWATBZOG-PL-110	bronze with shiny opal	110 - 130V
GAIWATBZSG-PL-110	bronze with smoked	110 - 130V
GAIWATBZHF-PL-110	bronze with smoked hand formed glass	110 - 130V
GAIWATSBMO-PL-110	satin brass with matt opal	110 - 130V
GAIWATSBOG-PL-110	satin brass with shiny opal	110 - 130V
GAIWATSBSG-PL-110	satin brass with smoked	110 - 130V
GAIWATSBHF-PL-110	satin brass with smoked hand fomed glass	110 - 130V

CTOLIGHTING

GAIA WALL TALL - WALL PLATE - DALI-A

FINISH

bronze with matt opal glass bronze with shiny opal glass bronze with smoked glass bronze with smoked hand formed glass satin brass with matt opal glass satin brass with shiny opal glass satin brass with smoked glass shade satin brass with smoked hand formed glass

DIMENSIONS (body of fixture)

 $150 \times 183 \times 350 \text{ mm} \text{ (w x d x h)}$

WEIGHT

1.5kg (3.3lbs)

ILLUMINATION

220-240v - 1 x E14 - 25w max (or 4.5w 2700k LED) DALI converter to be installed in the cavity

DIMMING

dimmable bulb required DALI compatible


WALL ROSE / PLATE

round wall plate - ø 114 x 5 mm (dia x d)


CERTIFICATION








*Diagrams are not to scale.











cover plate dimensions







SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
GAIWATBZMO-PL-DALIA-240	bronze with matt opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATBZOG-PL-DALIA-240	bronze with shiny opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATBZSG-PL-DALIA-240	bronze with smoked glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATBZHF-PL-DALIA-240	bronze with smoked hand formed glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATSBMO-PL-DALIA-240	satin brass with matt opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATSBOG-PL-DALIA-240	satin brass with shiny opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATSBSG-PL-DALIA-240	satin brass with smoked glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V
GAIWATSBHF-PL-DALIA-240	satin brass with smoked hand formed glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall cavity	220 - 240V