# CTQLIGHTING

# PENDULUM PENDANT

#### FINISH

bronze with smoked glass satin brass with smoked glass

# DIMENSIONS (body of fixture)

320 x 150 x 525 mm (w x d x h)

### WEIGHT

8kg (17.6lbs) please ensure ceiling structure is strong enough to support the weight of the light

### OVERALL DROP

minimum 665 mm maximum on request 3645 mm supplied with 1000 mm drop rod

# ILLUMINATION

220-240v - integrated LED - 8w - 2700K 110-130v - integrated LED - 8w - 2700K LED driver to be installed in the ceiling rose drivers must be installed up to 20 meters from the body of the light


#### DIMMING


trailing edge dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only) 0/1-10v (220-240v or 110-130v) - on request

### CEILING ROSE / PLATE


round ceiling rose - ø 45 x 120 mm (dia x h)

# CERTIFICATION











mounting plate dimensions



North America junction box cover



\*Diagrams are not to scale.

SKU NUMBER	FINISH DESCRIPTION	VOLTAGE
PENPEOBZSG-240	bronze with smoked glass	220 - 240V
PENPEOSBSG-240	satin brass with smoked glass	220 - 240V
PENPEOBZSG-110	bronze with smoked glass	110 - 130V
PENPEOSBSG-110	satin brass with smoked glass	110 - 130V

# CTOLIGHTING

# PENDULUM PENDANT - DALI-A

#### FINISH

bronze with smoked glass satin brass with smoked glass

#### DIMENSIONS (body of fixture)

320 x 150 x 525 mm (w x d x h)

#### WEIGHT

8kg (17.6lbs) please ensure ceiling structure is strong enough to support the weight of the light

#### OVERALL DROP

minimum 665 mm maximum on request 3645 mm supplied with 1000 mm drop rod

#### ILLUMINATION

integrated LED - 8w - 2700K DALI LED driver to be installed in the ceiling cavity drivers must be installed up to 20 meters from the body of the light

#### DIMMING


DALI compatible


#### CEILING ROSE / PLATE

round ceiling rose - ø 45 x 120 mm (dia x h)

#### CERTIFICATION









\*Diagrams are not to scale.

1.8)			
120mm (4.7)	min 20mm (0.8)		
	525mm (		



320mm (12.6)





LED driver dimensions 120mm (4.7)

Ē

SKU NUMBER FINISH DESCRIPTION TYPE OF DALI	VOLTAGE
PENPEOBZSG-DALIA-240 bronze with smoked glass DALI A included - For ligalterations. Dali can be	ghts that do not require aesthetic fitted inside the ceiling/wall cavity 220 - 240V
	ghts that do not require aesthetic fitted inside the ceiling/wall cavity 220 - 240V



# CTQLIGHTING

# **PENDULUM PENDANT - DALI-B**

#### FINISH

bronze with smoked glass satin brass with smoked glass

#### DIMENSIONS (body of fixture)

320 x 150 x 525 mm (w x d x h)

#### WEIGHT

8kg (17.6lbs) please ensure ceiling structure is strong enough to support the weight of the light

#### OVERALL DROP

minimum 580 mm maximum on request 3560 mm supplied with 1000 mm drop rod

#### ILLUMINATION

integrated LED - 8w - 2700K DALI LED driver to be installed in the ceiling rose

DIMMING


DALI compatible


# **CEILING ROSE / PLATE**

round ceiling rose - ø 140 x 35 mm (dia x h)

#### CERTIFICATION


# 






\*Diagrams are not to scale.

320mm (12.6)		
I		
	150mm (5.9	





SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
PENPEOBZSG-DALIB-240	bronze with smoked glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V
PENPEOSBSC-DALIB-240	satin brass with smoked glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V

